



25
YEAR GUARANTEE

LOCK-MAT[®] COMFORT

For durable flooring that also provides support in areas that require prolonged standing, the Lock-Mat Comfort is the ideal choice. Lock-Mat Comfort offers the perfect combination of safety and comfort, as well as the ease and speed of installation that you'd expect from any Flexi-Tile flooring product.

Manufactured to the highest quality standards, Lock-Mat Comfort tiles are expertly designed using a patented ergonomic system, making them perfect for areas that require prolonged periods of standing, helping to stimulate circulation and reducing tiredness in the back and legs. Ideal for factory production lines, workshops, garages and play areas, the Lock-Mat Comfort is the first choice when it's important to support people's comfort whilst providing a safe and durable flooring system.

At 17mm thick, the Lock-Mat Comfort is hard-wearing, tough and designed for prolonged use. The dimpled surface is not only designed for ergonomic purposes, but also improves heat insulation by giving protection against cold flooring beneath. Lock-Mat Comfort also helps to reduce the chance of breakage of fallen objects whilst providing improved noise-reduction capabilities.

Benefits & features of this product are:

- Ergonomic design supports legs and back
- Interlocking PVC tile
- Easy installation
- Low maintenance
- Anti-slip
- Resistant to most chemicals
- 100% recyclable
- Sound absorbing
- Anti-fatigue
- Resists punctures & abrasions
- Reaction to fire performance- BFL-S1

Colour Options

Lock-Mat[®] tiles are available in the following colours:



N.B: Other colours are available depending on quantity required. Colours shown above may vary from colour of manufacture.



LOCK-MAT® COMFORT Technical Specification

Normes Standards	Material (PVC) Weight (kg)	Polyvinyl Chloride 2.5 kg / tile
	Tile Dimensions	500mm ²
BS EN 428	Thickness	17 ± 0.2
BSEN 423	Staining Resistance	√
BS EN 425	Castor Chair Suitability	√
BS EN 427	Squareness & Straightness	<0.04
BS EN 660-2	Abrasion Resistance (wear group)	T
BS EN 649	Class 34/43 - Commercial . Very Heavy/ Light Industrial	√
BS EN 435	Flexibility (mm)	No cracking at 10mm
BS EN 20105	B02 Light Fastness	>7
BS EN 433	Residual Indentation (mm)	≤0.10
BS EN ISO 140-8	Impact Noise Reduction (dB)	16
BS EN 434	Dimensional Stability (%)	0.01
BS EN 434	Curling After Exposure Heat (mm)	0.04
BS EN 14041	European Building Standard	√
EN 13501	Reaction To Fire Performance	Bfl-S1
EN 14184	Formaldehyde Content (Class)	E1 (CWFT)
BS EN 12667	Thermal Resistance	0.1638 W/(mK)
EN 1081	Electrical Resistance (ohms)	≤10 ¹³ Ω
BS EN 1815	Static Electrical Procomfortsity (kv)	<2.0
BS EN 13893	Slip Resistance (class)	DS
DIN 51130	German Standard Slip Resistance	R10

For more information contact :

Telephone: +44 (0) 2892 667 264 **Email:** sales@flexi-tile.com

Riverbank, The Green, Lisburn, BT27 5SR, Northern Ireland, UK

www.flexi-tile.com is part of the Unicorn Group