

10 YEAR WARRANTY **Expected Lifespan 20+ Years**

UNICORN TILE 10MM TEXTURED

Unicorn Tile 10mm is our most robust tile and at 10mm thick it can withstand moving workloads greater than 1000kg all whilst being loose laid, no adhesive required*. The daily use of forklifts, pallet trucks and other heavy production machinery is possible with this tile and the strong interlocking system reduces dust and dirt underfoot. Unicorn Tile 10 mm is also an excellent alternative to continually painting your floor.

Applications



Industrial



Factory



Distribution Centre



Warehouse



Hanger Facilities

Standard Colours



Dark Grey




Light Grey



Black



Blue



Yellow



Green



Red



Extreme durability - can handle HGV's



Can be laid on cracked, damor damaged floors



No adhesives*



Anti-Slip properties



Protects



Easy Installation



Enviromentally friendly



Low Maintenance



Resistant to most chemicals

For details when adhesive is required see wheel guide



UNICORN TILE 10MM TEXTURED Technical Specification

STANDARD	Material (PVC)	Polyvinyl Chloride
	Weight (kg)	3.2kg (+/- 50g)
	Tile Dimentions	490 x 490mm
BS EN 428	Thickness	10 ± 0.2
BS EN 423	Staining Resistance	√
BS EN 425	Castor Chair Suitability	√
BS EN 427	Squareness & Straightness	<0.05
BS EN 660-2	Abrasion Resistance (Wear Group)	T
BS EN 649	Class 34 - Commercial/Very Heavy	√
BS EN 649	Class 43 - Light Industrial/Very Heavy	√
BS EN 20105	B02 Light Fastness	>7
BS EN 433	Residual Indentation (mm)	≤0.10
BS EN ISO 140-8	Impact Noise Reduction (Db)	16
BS EN 434	Dimensional Stability (%)	0.11
BS EN 434	Curling After Exposure Heat (mm)	0.15
BS EN 14041	European Building Standard	√
BS EN 13501	Reaction To Fire Performance	Bfl-S1
BS EN 14184	Formaldehyde Content (Class)	E1 (CWFT)
BS EN 12667	Thermal Resistance (m2 K/W)	0.03807
EN 1081	Electrical Resistance (Ohms)	≤10 ⁴ Ω
BS EN 1815	Static Electrical Propensity (Kv)	<2.0
BS EN 13893	Slip Resistance (Class)	DS
DIN 51130	German Standard Slip Resistance	R10
DIN 53516	Mechanical Resistance	17N/mm2
EC 19072006	Reach Compliant	√
SHORE A	Hardness	92

For more information contact us now: **Tel:** +44 (0) 28 9262 5898 | **Email:** info@flexi-tile.com
Riverview, The Green, Lisburn, BT27 5SR, Northern Ireland, UK

www.flexi-tile.com is part of the Unicorn Group