



10 YEAR WARRANTY **Expected Lifespan 20+ Years**

UNICORN TILE 5MM GRANITE

The stunning Granite collection provides an elegant and contemporary design feature for commercial and domestic flooring. The tiles are designed to reflect the visual beauty and strength that natural Granite possesses, providing the perfect alternative to traditional ceramic and stone tiled flooring.

Applications



Retail



Schools



Showrooms



Domestic



Gym



Contemporary finish



Sound absorbing



Affordable alternative to real granite



Anti-Slip properties



Protects



Easy Installation



Environmentally friendly



Low Maintenance



Resistant to most chemicals



UNICORN TILE 5MM GRANITE Technical Specification

STANDARD	Material (PVC)	Polyvinyl Chloride
	Weight (kg)	1.5 kg (+/- 50g)
	Tile Dimentions	490 x 490mm
BS EN 428	Thickness	4.5 ± 0.2
BS EN 423	Staining Resistance	√
BS EN 425	Castor Chair Suitability	√
BS EN 427	Squareness & Straightness	<0.05
BS EN 660-2	Abrasion Resistance (Wear Group)	T
BS EN 649	Class 34 - Commercial/Very Heavy	√
BS EN 649	Class 43 - Light Industrial/Very Heavy	√
BS EN 20105	B02 Light Fastness	>7
BS EN 433	Residual Indentation (mm)	≤0.10
BS EN ISO 140-8	Impact Noise Reduction (Db)	16
BS EN 434	Dimensional Stability (%)	0.11
BS EN 434	Curling After Exposure Heat (mm)	0.15
BS EN 14041	European Building Standard	√
BS EN 13501	Reaction To Fire Performance	Bfl-S1
BS EN 14184	Formaldehyde Content (Class)	E1 (CWFT)
BS EN 12667	Thermal Resistance (m2 K/W)	0.03807
EN 1081	Electrical Resistance (Ohms)	≤1014Ω
BS EN 1815	Static Electrical Propensity (Kv)	<2.0
BS EN 13893	Slip Resistance (Class)	DS
DIN 51130	German Standard Slip Resistance	R10
DIN 53516	Mechanical Resistance	17N/mm2
EC 19072006	Reach Compliant	√
SHORE A	Hardness	92

For more information contact us now: **Tel:** +44 (0) 28 9262 5898 | **Email:** info@flexi-tile.com
Riverview, The Green, Lisburn, BT27 5SR, Northern Ireland, UK

www.flexi-tile.com is part of the Unicorn Group